200w Solar Flood Light

Model - SFSOLFL200UNI-LI



The Sunfor Univeral Solar street light is slimline, compact and aesthetically pleasing which incorporates all components together in a modern and robust design. This model is supplied with a 200w Philips SMD LED with a lumen output of 130lm/w. Lighting profile 5Hrs 100%, 8Hrs 70% as standard to increase battery life & performance Designed to operate for 13 hours per night The battery requires 5 hours to replenish. Multiple LED luminaire options for different lighting applications with lens options Smart 365 technology ensuring your light runs all year. Distribution as standard is a 120 degree design. Designed for easy maintenance without having to remove the system from the pole or solar panels. This model is supplied with multiple solar panels



local stock dependent



Model - SFSOLFL200UNI-LI

| | Power | 200w |
|---------------------------------------|--|-------------------------------|
| | LED | Philips |
| LIGHT | IP Rating | IP 65 |
| | Flux @ CCT 5700 - 6000K | 26000 |
| | CRI - Colour Rendering Index | 80 |
| | Optical control | Glass Lens |
| | Average Lifespan | 10 years |
| | Operating temperature | -30 Deg ~ + 45 Deg |
| | Mounting height | 10 meter above surface |
| | Beam angle | 120 Degree |
| | Lumen per watt | 130 |
| | Pole to pole distance | 50 meters |
| | Lithium | Sharp |
| | Voltage | 22.2v |
| BATTERY | Watt Hours | 3396,60Wh |
| | Lifespan | 1000 cycles |
| ~ | Power | 540w |
| SOLAR | Voltage | 76.16v |
| PANEL | Maximum current | 9,37Amp |
| | Charging method | MPPT |
| | Dimming parameters | 100 / 70 / 50 & 30% |
| | Day night sensor | Integrated Day / Night sensor |
| CONTROLLER | Lighting parameters | 4 stage programmable |
| l [| <u> </u> | Temperature compensation |
| | Electrical parameters | Overheating, overcharging and |
| | | over discharging protections |
| BATTERY CRADLE AND ENCLOSURE | A Grade steel treated with anti rust and powder coated Manufactured in an SABS approved facility with ISO 9001 | |
| POLE | Galvanized with an option to powder coat - 12m (139 - 127 collar) | |
| WARRANTY | 3 years on all components - option to extend | |

